

INTERNATIONAL ELECTROTECHNICAL COMMISSION

IEC TR 61282-14
Edition 1.0 2016-01

FIBRE OPTIC COMMUNICATION SYSTEM DESIGN GUIDES –

**Part 14: Determination of the uncertainties
of attenuation measurements in fibre plants**

CORRIGENDUM 1

Replace the existing Table C.1 with the following new table:

Table C.1 – Spectral attenuation coefficients

	Domain nm	α_0	α_1	α_2	α_3	α_4	α_5	α_6
MM A1	800 to 1 350	$5,241\ 88 \times 10^{-01}$	$2,937\ 83 \times 10^{-03}$	$6,850\ 36 \times 10^{-06}$	$8,485\ 88 \times 10^{-09}$	$5,883\ 55 \times 10^{-12}$	$-2,163\ 8 \times 10^{-15}$	$3,297\ 25 \times 10^{-19}$
SM B1.3	1 285 to 1 385	$-7,510\ 8 \times 10^{-02}$	$1,719\ 89 \times 10^{-04}$	$1,309\ 54 \times 10^{-07}$	$3,318\ 81 \times 10^{-11}$	0	0	0
SM B1.3	1 385 to 1 675	$1,375\ 6 \times 10^{-01}$	$3,623\ 94 \times 10^{-04}$	$3,586\ 79 \times 10^{-07}$	$1,579\ 87 \times 10^{-10}$	$2,612\ 47 \times 10^{-14}$		